

Constellio config

Create Solr collection

- Requires Constellio 9.1+
- Stop Solr and Constellio



Replace all <name> and <name2> below with customer name or testing name and <ID> with their ID

Constellio config

- Create a file `tenants.json` file in `constellio/conf/` :
Warning make sure not to have an extra , for the final item as the parser crashes

```
[  
  {  
    "name": "<name>",  
    "code": "<name>",  
    "id": 1,  
    "hostnames": [  
      "<name>.cloud.constellio.com"  
    ]  
  },  
  {  
    "name": "<name2>",  
    "code": "<name2>",  
    "id": 2,  
    "hostnames": [  

```

json

Constellio config

Create Solr collection

```

    "<name2>.cloud.constellio.com"
  ]
}
....
]

```



- Create the tenant folder:
 - Create a new config folder for all the tenants:
 - `mkdir /opt/constellio/conf/tenants<id>`
 - Copy over the needed files:
 - `cp -r constellio.properties constellio.setup.properties license.xml settings tenant<id>`
 - Edit the `constellio.properties` in the tenant folder to add the collection settings and change the folder for content and transaction log:

```

dao.records.collection=<records_collection_name>
dao.events.collection=<events_collection_name>
dao.notifications.collection=<notifications_collection_name>
...
dao.contents.filesystem.folder=/opt/constellio/contents<id>
secondTransactionLog.folder=/opt/constellio/transaction_log<id>

```


properties

- Copy over the contents and transaction_log
 - `cp -r /opt/constellio/contents /opt/constellio/contents<id>`
 - `cp -r /opt/constellio/transaction_log/ /opt/constellio/transaction_log<id>`
- Change the permission for the new files:
 - `sudo chown -R constellio-service:constellio /opt/constellio/`

Constellio config

Create Solr collection

Create Solr collection

- Copy the current core config into new folders, make a set for all the new tenants 
 - `cp -r /var/solr/configsets/records_configs /var/solr/configsets/<records_collection_name>`
 - `cp -r /var/solr/configsets/events_configs /var/solr/configsets/<events_collection_name>`
 - `cp -r /var/solr/configsets/notifications_configs /var/solr/configsets/<records_collection_name>`
- For all the new core edit the `core.properties` properties to match the name with the new name `<records_collection_name>`, `<events_collection_name>`, `<notifications_collection_name>`
- Make sure all the new cores have the correct permission
 - `sudo chown -R solr-service:constellio /var/solr/configsets/`
- Restart Solr to enable the new collections